

MILAN S.r.l. a socio unico

Head Office – Export department:
 Viale Europa, 74
 20090 Cusago (MI) Italy
 T. +39 02 9039.4556-4158
 F. +39 02 9039.4551
 www.taskercables.com

Ufficio Commerciale e Centro Distribuzione
 Viale Europa 72 Strada F12
 20090 Cusago (MI) Italy
 T. +39 02 9039.0037-0059
 F. +39 02 9039.0049
 www.tasker.it

Technical Datasheet

tasker® C116 - 4x0,14 mm² Spiral Shielded Cable



NOTE The picture don't represent the real number of conductors.
CATEGORY Spiral Shielded Cable (See Audio Catalogue)
APPLICATIONS Sound Reproductions and Electronics.

- A:** Soft Black PVC.
Outer Cable Diam. Ø 5,20 (±0,10) mm.
- B:** The single conductors are shielded with O.F.C. red copper spiral covering 100%.
- C:** Core Insulation with PVC, colored Black, White, Red, Yellow.
Core Diam. Ø 1,30 (±0,10) mm.
- D:** O.F.C. red copper stranded formation 18x0,10 mm.
Nom. Cross section 4x0,14 mm².

MARKING tasker® C116 4x0,14 mm² O.F.C. Individually Shielded Cable
CUSTOM This product may be custom produced also in L.S.Z.H. polymer, PE, PUR,
PRODUCTION or Metallic Armored.

Cable Properties

Conductor Resistance	138 Ω/Km
Capacity Core/Core	150 pF/mt
Capacity Core/Shield	290 pF/mt
Max Rated Voltage	49 V
Operative Temperature	-15/+70°C

USE	X	Indoor	Interno Edificio	INSTALLATION	X	Fixed	Fissa	INFORMATION	X	RoHS2 Compliant
Impiego		Outdoor Limited	Esterno Limitato	Posa	X	Restricted Mobile	Mobile Limitata	Informazioni	X	Ver. A / 26.05.17
		Outdoor	Esterno			Mobile	Mobile			
		Outdoor Direct Burial	Esterno Interrato			Mobile in Drag Chain	Mobile in Catena			