

MILAN S.r.l. a socio unico

**Head Office – Export department:**  
 Viale Europa, 74  
 20090 Cusago (MI) Italy  
 T. +39 02 9039.4556-4158  
 F. +39 02 9039.4551  
 www.taskercables.com

**Ufficio Commerciale e Centro Distribuzione**  
 Viale Europa 72 Strada F12  
 20090 Cusago (MI) Italy  
 T. +39 02 9039.0037-0059  
 F. +39 02 9039.0049  
 www.tasker.it

## Technical Datasheet

# tasker® C161 – 24x0,25 mm<sup>2</sup>

## Flexible Multi Conductor Cable



**NOTE**  
**CATEGORY**  
**APPLICATIONS**

The picture does not represent the real number of conductors.  
 Multi Conductor Cable (See Electronics Catalogue)  
 wiring and electronics

- A:** Black Soft **PVC** Sheath.  
Outer Diam. Ø 9,80 (±0,10) mm.
- B:** Cores Insulation with Soft **PVC** sheaths.  
DIN 47100 Standards – White, Brown, Green, Yellow, Grey, Pink, Blue, Red, Black, Violet, Grey/Pink, Red/Blue, White/Green, Brown/Green, White/Yellow, Yellow/Brown, White/Grey, Grey/Brown, White/Pink, Pink/Brown, White/Blue, Brown/Blue, White/Red, Brown/ Red.  
Diam. Ø 1,40 (±0,20) mm.
- C:** Stranded O.F.C. Red Copper formation 8x0,20 mm.  
Nom. Cross section 24x0,25 mm<sup>2</sup>.

**MARKING**  
**CUSTOM**  
**PRODUCTION**

**tasker® C 161 SHEATHED CABLE ITALY**  
 This product may be custom produced also in **L.S.Z.H.** polymer, **PE, PUR,** or Metallic Armored.

### Cable Properties

|                              |            |
|------------------------------|------------|
| <b>Conductor Resistance</b>  | 75,85 Ω/Km |
| <b>Max Rated Voltage</b>     | 49 V       |
| <b>Operative Temperature</b> | -15/+70°C  |

|                |          |                       |                   |                     |          |                      |                  |                     |          |                   |
|----------------|----------|-----------------------|-------------------|---------------------|----------|----------------------|------------------|---------------------|----------|-------------------|
| <b>USE</b>     | <b>X</b> | Indoor                | Interno Edificio  | <b>INSTALLATION</b> | <b>X</b> | Fixed                | Fissa            | <b>INFORMATION</b>  | <b>X</b> | RoHS2 Compliant   |
| <b>Impiego</b> |          | Outdoor Limited       | Esterno Limitato  | <b>Posa</b>         | <b>X</b> | Restricted Mobile    | Mobile Limitata  | <b>Informazioni</b> | <b>X</b> | Ver. A / 26.05.17 |
|                |          | Outdoor               | Esterno           |                     |          | Mobile               | Mobile           |                     |          |                   |
|                |          | Outdoor Direct Burial | Esterno Interrato |                     |          | Mobile in Drag Chain | Mobile in Catena |                     |          |                   |