



MILAN S.r.l. a socio unico

Head Office – Export department:
 Viale Europa, 74
 20090 Cusago (MI) Italy
 T. +39 02 9039.4556-4158
 F. +39 02 9039.4551
 www.taskercables.com

Ufficio Commerciale e Centro Distribuzione
 Viale Europa 72 Strada F12
 20090 Cusago (MI) Italy
 T. +39 02 9039.0037-0059
 F. +39 02 9039.0049
 www.tasker.it

Technical Datasheet  

tasker® C263 – 5x0,08 mm² (75 Ω)

Special Multi Mini Coax Video cable



A	B	C	D	E
---	---	---	---	---

CATEGORY Coaxial cable 75 Ω (See Video Catalogue)
APPLICATIONS Professional video transmission systems and monitors.

- A:** Grey **Flame Retardant PVC** Sheath. Outer Diam. Ø 9,80 (±0,20) mm.
- B:** Soft **PVC** Sheath on single conductors. Diam. Ø 2,80 (±0,20) mm.
Colored: Red, Green, Blue, Black and White.
- C:** Shielding in O.F.C. tinned copper spiral covering 100%.
- D:** Core Insulation with PEE – Diam. Ø 1,60 (±0,20) mm.
- E:** Stranded formation in O.F.C. red copper, 10x0,10 mm.
Nom. Cross section 5x0,08 mm² (75Ω).

MARKING tasker® C263 5x75Ω O.F.C. Multicoaxial Video Cable
CUSTOM This product may be custom produced also in **L.S.Z.H.** polymer, **PE, PUR,**
PRODUCTION with or without Metallic Armor.

Cable Properties

Conductor Resistance	203 Ω/Km
Capacity Core/Shield	67 pF/mt
Velocity of Propagation	66%
Impedance	75 Ω
Max Rated Voltage	49 V
Operative Temperature	-20/+70°C

Attenuation dB/100 mt.

50 MHz	19,50
100 MHz	28,50
200 MHz	47,70
400 MHz	60,20
800 MHz	87,30
1000 MHz	103,00

USE	X	Indoor	Interno Edificio	INSTALLATION	X	Fixed	Fissa	INFORMATION	X	RoHS2 Compliant
Impiego	X	Outdoor Limited	Esterno Limitato	Posa	X	Restricted Mobile	Mobile Limitata	Informazioni	X	Ver. A / 16.05.17
		Outdoor	Esterno			Mobile	Mobile			
		Outdoor Direct Burial	Esterno Interrato			Mobile in Drag Chain	Mobile in Catena			