

MILAN S.r.l. a socio unico

Head Office – Export department:
 Viale Europa, 74
 20090 Cusago (MI) Italy
 T. +39 02 9039.4556-4158
 F. +39 02 9039.4551
 www.taskercables.com

Ufficio Commerciale e Centro Distribuzione
 Viale Europa 72 Strada F12
 20090 Cusago (MI) Italy
 T. +39 02 9039.0037-0059
 F. +39 02 9039.0049
 www.tasker.it

Technical Datasheet

tasker® C4015 – 4x0,15 mm² Braided Shielded Tinned Cable



NOTE
CATEGORY
APPLICATIONS

The picture does not represent the real number of conductors
 Braided Conductor Shielded Cable (See Data Network Catalogue)
 Data transmission and Electronics

- A:** Grey Soft **PVC** Sheath.
Outer cable diam. Ø 4,30 (±0,20) mm.
- B:** Braided Shielding O.F.C. Tinned Copper covering 85%
- C:** Cores Insulation with Soft **PVC**. Core color code with DIN 47100 Standards.
Stranded with waste filler between conductors and wrapped with Mylar Tape.
Diam. Ø 1,20 (±0,20) mm.
- D:** Stranded O.F.C. Tinned Copper formation 19x0,10 mm.
Nom. Cross section 4x0,15 mm²

MARKING

tasker® C4015 4x0,15 - 25 AWG Professional Data Transmission Shielded Cable - Made in Italy

CUSTOM PRODUCTION

This product may be custom produced also in **L.S.Z.H.** polymer, **PE, PUR,** or Metallic Armored.

Cable Properties

Conductor Resistance	118 Ω/Km
Capacity Core/Core	120 pF/m
Capacity Core/Shield	230 pF/m
Max Rated Voltage	49 V
Operative Temperature	-15/+70°C

USE	X	Indoor	Interno Edificio	INSTALLATION	X	Fixed	Fissa	INFORMATION	X	RoHS3 Compliant
Impiego		Outdoor Limited	Esterno Limitato	Posa	X	Restricted Mobile	Mobile Limitata	Informazioni	X	Ver. B / 26.05.19
		Outdoor	Esterno			Mobile	Mobile			
		Outdoor Direct Burial	Esterno Interrato			Mobile in Drag Chain	Mobile in Catena			