

MILAN S.r.l. a socio unico

Head Office – Export department:
 Viale Europa, 74
 20090 Cusago (MI) Italy
 T. +39 02 9039.4556-4158
 F. +39 02 9039.4551
 www.taskercables.com

Ufficio Commerciale e Centro Distribuzione
 Viale Europa 72 Strada F12
 20090 Cusago (MI) Italy
 T. +39 02 9039.0037-0059
 F. +39 02 9039.0049
 www.tasker.it

Technical Datasheet

tasker® C525 – 1x0,70 mm²

Low Loss Coaxial cable 50 Ω



A	B	C	D	E
---	---	---	---	---

CATEGORY Coaxial cable 50 Ω (See Data Network Catalogue)
APPLICATIONS High Frequency Antennas and Networks.

- A:** Black PVC - RAL 9004 - Outer Diam. Ø 5,00 (±0,20) mm
- B:** First Shielding in O.F.C. tinned copper Braid covering 96%
- C:** Second Shielding in Aluminum/PET/Aluminum covering 100%
- D:** Core Insulation with White polyethylene (PE).
Diam. Ø 2,80 (±0,20) mm
- E:** Red Copper Stiff Wire formation 1x0,95 mm.
Nom. Cross section 1x0,70 mm².

MARKING tasker® C525 1x0,70 mm² (50Ω) - 0.95/2.80/5.00 - DOUBLE SHIELDED LOW LOSS WI-FI / RF COAX CABLE MADE IN ITALY

CUSTOM PRODUCTION This product may be custom produced also in L.S.Z.H. polymer, PE, PUR, with or without Metallic Armor.

Cable Properties

Conductor Resistance	18 Ω/Km
Capacity Core/Shield	80 pF/m
Velocity of Propagation	80%
Impedance	50Ω
Insulation Spark Test	4,0 kV
Operative Temperature	-15/+70°C

Attenuation dB/100 m and Max Watt (W) Applicable

50 MHz	8,50	626
100 MHz	11,30	443
500 MHz	25,90	198
800 MHz	33,20	157
1000 MHz	37,50	140
3000 MHz	73,40	81

USE	<input checked="" type="checkbox"/>	Indoor	Interno Edificio	INSTALLATION	<input checked="" type="checkbox"/>	Fixed	Fissa	INFORMATION	<input checked="" type="checkbox"/>	RoHS3 Compliant
Impiego		Outdoor Limited	Esterno Limitato	Posa	<input checked="" type="checkbox"/>	Restricted Mobile	Mobile Limitata	Informazioni	<input checked="" type="checkbox"/>	Ver. A / 17.06.19
		Outdoor	Esterno			Mobile	Mobile			
		Outdoor Direct Burial	Esterno Interrato			Mobile in Drag Chain	Mobile in Catena			