

MILAN S.r.l. a socio unico

Head Office – Export department:
 Viale Europa, 74
 20090 Cusago (MI) Italy
 T. +39 02 9039.4556-4158
 F. +39 02 9039.4551
 www.taskercables.com

Ufficio Commerciale e Centro Distribuzione
 Viale Europa 72 Strada F12
 20090 Cusago (MI) Italy
 T. +39 02 9039.0037-0059
 F. +39 02 9039.0049
 www.tasker.it



rightly blue

Technical Datasheet

tasker® C700 S.-F.T.P Special LAN Cable



CATEGORY Twisted Pair LAN Cable (See Data Network Catalogue)
APPLICATIONS High Frequency Transmission Data

- A:** Soft Night Blue PVC sheath.
Outer cable diam. Ø: 7,00 (±0,10) mm.
- B:** First Shielding with a Braid of O.F.C. tinned copper covering 70% + tinned copper Drain Wire.
- C:** Second shielding with Aluminum tape, covering 100%.
- D:** The four pairs are stranded together with polyester based tape.
- E:** Insulation with PE, diam. Ø 0,90 (±0,10) mm.
Core colors: white-blue/Blue, white-orange/Orange, white-green/Green, white-brown/Brown.
- F:** Stranded formation of 7x0,15 mm in O.F.C. Red Copper.
Nom. Cross section 5x2x0,14 mm².

MARKING tasker® C700 5x2x0,14 mm² Flex Data Twisted Pair Cable Made in Italy
CUSTOM This product may be custom produced also in L.S.Z.H. polymer, PE, PUR,
PRODUCTION with or without Metallic Armor.

Cable Properties

Conductor Resistance	138 Ω/Km
Impedance	100 Ω
Max Rated Voltage	49 V
Operative Temperature	-15/+70°C

USE	<input checked="" type="checkbox"/>	Indoor	Interno Edificio	INSTALLATION	<input checked="" type="checkbox"/>	Fixed	Fissa	INFORMATION	<input checked="" type="checkbox"/>	RoHS2 Compliant
Impiego		Outdoor Limited	Esterno Limitato	Posa	<input checked="" type="checkbox"/>	Restricted Mobile	Mobile Limitata	Informazioni	<input checked="" type="checkbox"/>	Ver. A / 26.05.17
		Outdoor	Esterno			Mobile	Mobile			
		Outdoor Direct Burial	Esterno Interrato			Mobile in Drag Chain	Mobile in Catena			