

MILAN S.r.l. a socio unico

Head Office – Export department:
 Viale Europa, 74
 20090 Cusago (MI) Italy
 T. +39 02 9039.4556-4158
 F. +39 02 9039.4551
 www.taskercables.com

Ufficio Commerciale e Centro Distribuzione
 Viale Europa 72 Strada F12
 20090 Cusago (MI) Italy
 T. +39 02 9039.0037-0059
 F. +39 02 9039.0049
 www.tasker.it

Technical Datasheet

tasker® C803 3x0,35 (75Ω)

Special Video Flat Divisible Cable



A	B	C	D	E
---	---	---	---	---

CATEGORY Flat divisible video cable (See Video Catalogue)
APPLICATIONS R.G.B.Video and Audio Stereo assembly

- A:** Night Blue Soft **PVC** Sheath.
Outer Dimension: 5,50x16,30 (±0,20) mm.
- B:** Braid shielding in of O.F.C. red copper, covering 85%.
- C:** Aluminum foil tape covering 100%.
- F:** Insulation with White PEE. Diam. Ø 3,00 (±0,20) mm.
- G:** Stranded O.F.C. red copper formation 30x0,12 mm.
Nom. Cross section 3x0,35 mm² (75Ω)

MARKING tasker® C803 3x0,35 mm² (75W) O.F.C. Sound Stream Digital AC-3DVD – RGB Cable
CUSTOM PRODUCTION This product may be custom produced also in **L.S.Z.H.** polymer, **PE** or **PUR**.

Video 75 Ω properties

Conductor Resistance	58,00 Ω/Km
Impedence	75 Ω
Velocity of Propagation	66 %
Capacity Core/Shield	63 pF/m
Max rated Voltage	49 V
Operative Temperature	-15/+70°C

Attenuation dB/100 m.

50 MHz	18,50
100 MHz	25,60
200 MHz	27,70
400 MHz	40,50
800 MHz	61,50
1000 MHz	85,30

USE	X	Indoor	Interno Edificio	INSTALLATION	X	Fixed	Fissa	INFORMATION	X	RoHS2 Compliant
Impiego		Outdoor Limited	Esterno Limitato	Posa	X	Restricted Mobile	Mobile Limitata	Informazioni	X	Ver. A / 26.05.17
		Outdoor	Esterno			Mobile	Mobile			
		Outdoor Direct Burial	Esterno Interrato			Mobile in Drag Chain	Mobile in Catena			