




- Ceiling mount design with concealed screw fixings
- Future proof UHF and cellular coverage
- Flame retardant halogen-free radome
- Low PIM and SAR tested to EN50385:2002

A true wideband system, Panorama's CMWB2-038-6-NJ allows businesses and facilities to support multi-service / multi-operator wireless coverage. A huge number of services are supported from 380MHz UHF to 6GHz - including TETRA UHF, GSM400, AWS 1700MHz, Quadband GSM, 3G UMTS, 2.4GHz WLAN, LTE & WiMAX etc. enabling simultaneous connectivity for employees, consumers and emergency services and providing in-building service providers and DAS installers with a convenient one size fits all solution.




This product features Panorama Antennas' PIM Guard Technology and will meet or exceed a third order intermodulation level of < -140dBc.*


Technical Specification




3D Gain Plot (400 MHz)




3D Gain Plot (450MHz)




3D Gain Plot (700MHz)




3D Gain Plot (800MHz)




3D Gain Plot (900MHz)




3D Gain Plot (1800MHz)




3D Gain Plot (1900MHz)




3D Gain Plot (2100MHz)




3D Gain Plot (2400MHz)




3D Gain Plot (2600MHz)




3D Gain Plot (3500MHz)



3D Gain Plot (5800MHz)



Typical VSWR*



*VSWR measured at antenna connector.

Part No.		CMWB2-038-6-NJ
Electrical Data		
Frequency Range (MHz)	380-6000	
Operational bands	UHF/2G/3G/4G/WLAN/WIMAX	
Radiation pattern	Omni-directional	
Typical VSWR	< 2.7:1	
Peak Gain	380-800MHz	2dBi
	800-1000MHz	3dBi
	1000-6000MHz	6dBi
Typical Passive intermod. (2x20W, 3rd ord.) dBc*	< -140	
SAR & 'Touch Safe' Test Data	According to 50385:2002 (Bands: 850,900,1800,2100MHz)	
Max input power (W)	60 Watts	
Impedance	50Ω	
Mechanical Data		
Dimensions (mm)	Height	155 (6.1")
	Diameter	266 (10.47")
Operating temp (°C)	-30° / +70°C (-22° / 158°F)	
Radome Material	Geloy PC/ASA	
Flame Retardance	UL94-5VB (chlorine and bromine free)	
Colour	White	
Mounting Data		
Fixing	4 x 6 mm fixing holes and/or N socket lock wheel	
Diameter (mm)	6 (0.24") / 16 (5/8")	
Depth (mm)	41 (1.6")	
Termination	N Socket	

*Range PIM performance verified at 1900MHz under controlled conditions by Anritsu PIM Master MW82119A-0190 test equipment.



Panorama Antennas Ltd
Frogmore, London, SW18 1HF, United Kingdom

T: +44 (0)20 8877 4444
F: +44 (0)20 8877 4477
E: sales@panorama-antennas.com
www.panorama-antennas.com

Waiver: The data given above is indicative of the performance of the product/s under particular conditions and does not imply a guarantee of performance or a warranty of fitness for any particular purpose. These specifications are subject to change without notice.

Copyright © Panorama Antennas Ltd. All rights reserved.