



KS-7B

CB fiberglass antenna 1,5 m (5') length


 There's no need to introduce this classic of CB marine communication. This antenna has become a standard for professionals, thanks to an excellent quality and an outstanding reliability. The KS-7B is built with a 1,4 mm thick fiberglass whip that gets fully foam injected with the special Scout 100% waterproof technique, and it's ice white colored with high gloss anti-UV filter to prevent color deterioration.

The antenna is supplied with 5m RG-58 MIL cable and 1 PL-259 connector to complete the installation on board.

 Non servono presentazioni per questo classico della comunicazione marittima CB, un'antenna che è diventata uno standard per i navigatori grazie anche alla sua qualità eccellente e ad una affidabilità al top della gamma.

La KS-7B è costruita con un corpo in vetroresina con spessore di 1,4 mm interamente riempito di poliuretano con la speciale tecnica Scout 100% waterproof, e verniciata con tonalità bianco ghiaccio e filtro anti-UV per prevenire il deterioramento del colore ai raggi solari.

Viene fornita con 5m di cavo RG-58 top performance a norme militari e un connettore PL-259 per completare l'installazione a bordo.

 Dieser Klassiker der CB Marinekommunikation bedarf keiner Erklärung. Diese Antenne ist dank ihrer herausragenden Qualität und exzellenten Zuverlässigkeit zum Standard für jeden Profi geworden.

Es hat einen 1,4mm Glasfaser Stab, der mit der speziellen 100% Waterproof Technik komplett schaumgefüllt ist, zusätzlich einen Hochglanz Anti UV- Filter, der die Farbe schützt.

Die Antenne wird mit 5 m RG-58 MIL-Kabel und 1 PL-259-Stecker geliefert, um die Installation an Bord abzuschließen.

- ▶ Foam injected - 100% WATERPROOF
- ▶ Anti - UV high gloss finish



Contents / Contenuto / Inhalt

1 x Antenna
1 x PL-259 (RG-58) male connector twist-on

Technical specifications

Frequency	27 MHz
Impedance	50 ohm
Electrical length	1/2 λ
V.S.W.R.	< 1,5:1
Polarization	Vertical
Max power input	10 W
Whip material	Fiberglass
Ferrule	Reinforced nylon
Coaxial cable	5 m RG-58 CU MIL
Mounting	1" x 14 thread
Length	1,5 m (5')
Weight	0,42 kilo

(code: PF AN NCB00002)

**5 YEAR
WARRANTY**

