

MILAN S.r.l. a socio unico

**Head Office – Export department:**  
 Viale Europa, 74  
 20090 Cusago (MI) Italy  
 T. +39 02 9039.4556-4158  
 F. +39 02 9039.4551  
 www.taskercables.com

**Ufficio Commerciale e Centro Distribuzione**  
 Viale Europa 72 Strada F12  
 20090 Cusago (MI) Italy  
 T. +39 02 9039.0037-0059  
 F. +39 02 9039.0049  
 www.tasker.it

## Technical Datasheet

# tasker® RG 59 BU 75 Ω Coaxial Mil. C 17 F Standard Cable



A	B	C	D
---	---	---	---

**CATEGORY**  
**APPLICATIONS**

Coaxial cable 75 Ω (See Video Catalogue)  
 Standard definition video applications and cable assembly

- A:** Black Soft **PVC** Sheath. Outer Diam. Ø 6,10 (±0,20) mm.
- B:** Shielding O.F.C. red copper Braid covering 95%.
- C:** Core Insulation with transparent compact PE. Diam. Ø 3,70 (±0,20) mm
- D:** Stiff Wire formation in CW 1x0,58 mm. Nom. Cross section 1x0,26 mm<sup>2</sup>

**MARKING**  
**AVAILABLE ALSO**

**tasker®** RG59 75 Ohm Mil.- C17/F Coaxial Video Cable Italy  
 RG59 BU, RG59 Flex, RG59 LSZH, RG59 eXtra, RG59 PUR,  
 RG59 AR

**CUSTOM**  
**PRODUCTION**

This product may be custom produced also in **PE**, with or without  
 Metallic Armor.

**Cable Properties**

<b>Conductor Resistance</b>	158 Ω/Km
<b>Capacity Core/Shield</b>	67 pF/m
<b>Velocity of Propagation</b>	66%
<b>Impedance</b>	75 Ω
<b>Max Rated Voltage</b>	2.000 V
<b>Operative Temperature</b>	-15/+70°C

**Attenuation dB/100 m.**

<b>100 MHz</b>	10,7
<b>200 MHz</b>	15,7
<b>400 MHz</b>	22,7
<b>600 MHz</b>	28,7
<b>800 MHz</b>	33,6
<b>1000 MHz</b>	38,0

<b>USE</b>	<b>X</b>	Indoor	Interno Edificio	<b>INSTALLATION</b>	<b>X</b>	Fixed	Fissa	<b>INFORMATION</b>	<b>X</b>	RoHS3 Compliant
<b>Impiego</b>		Outdoor Limited	Esterno Limitato	<b>Posa</b>	<b>X</b>	Restricted Mobile	Mobile Limitata	<b>Informazioni</b>	<b>X</b>	Ver. B / 16.05.19
		Outdoor	Esterno			Mobile	Mobile			
		Outdoor Direct Burial	Esterno Interrato			Mobile in Drag Chain	Mobile in Catena			