

MILAN S.r.l. a socio unico

Head Office – Export department:
 Viale Europa, 74
 20090 Cusago (MI) Italy
 T. +39 02 9039.4556-4158
 F. +39 02 9039.4551
 www.taskercables.com

Ufficio Commerciale e Centro Distribuzione
 Viale Europa 72 Strada F12
 20090 Cusago (MI) Italy
 T. +39 02 9039.0037-0059
 F. +39 02 9039.0049
 www.tasker.it

FirestoP® Technical Datasheet *rightly blue®*

tasker® TSK1066 – 5x(0.60/2.80/4.50)
Special Multi Coax Video cable 75 Ω



A	B	C	D	E	F	G
---	---	---	---	---	---	---

CATEGORY Multi Coaxial cable 75 Ω (See Video Catalogue)
APPLICATIONS Broadcast and video mixers.

- A:** Blue Night **Flame Retardant PVC** Sheath. Outer diam. Ø 14,70 (±0,20) mm.
- B:** Total taping in unweaved polyester.
- C:** Soft PVC Sheath on single conductors.
Color Code: Red, Green, Blue, Black and White. Diam. Ø 4,50 (±0,20) mm.
- D:** First Shielding in O.F.C. tinned copper braid covering 90%.
- E:** Second Shielding in aluminum foil tape covering 100%.
- F:** Core Insulation in FOAM PE. Diam. Ø 2,80 (±0,20) mm.
- G:** Stiff wire formation in O.F.C. red copper, 1x0,61 mm.
Nom. Cross section 5x0,29 mm² (75Ω).

MARKING **tasker®** TSK1066 - 5x75 ohm - MultiChannel Digital Video Cable - Made in Italy
CUSTOM This product may be custom produced also in **LSZH, PE, PUR,**
PRODUCTION with or without Metallic Armor.

Cable Properties

Conductor Resistance	61 Ω/Km
Capacity Core/Shield	56 pF/m
Velocity of Propagation	78%
Impedance	75 Ω
Max Rated Voltage	49 V
Operative Temperature	-20/+70°C

Attenuation dB/100 m.

30 MHz	6,2
100 MHz	11,3
200 MHz	15,0
300 MHz	18,2
500 MHz	24,0
1000 MHz	36,0

USE	X	Indoor	Interno Edificio	INSTALLATION	X	Fixed	Fissa	INFORMATION	X	RoHS2 Compliant
Impiego		Outdoor Limited	Esterno Limitato	Posa	X	Restricted Mobile	Mobile Limitata	Informazioni	X	Ver. A / 16.05.17
		Outdoor	Esterno			Mobile	Mobile			
		Outdoor Direct Burial	Esterno Interrato			Mobile in Drag Chain	Mobile in Catena			