

MILAN S.r.l. a socio unico

**Head Office – Export department:**  
 Viale Europa, 74  
 20090 Cusago (MI) Italy  
 T. +39 02 9039.4556-4158  
 F. +39 02 9039.4551  
 www.taskercables.com

**Ufficio Commerciale e Centro Distribuzione**  
 Viale Europa 72 Strada F12  
 20090 Cusago (MI) Italy  
 T. +39 02 9039.0037-0059  
 F. +39 02 9039.0049  
 www.tasker.it

## Technical Datasheet

# tasker® C119 – 4x0,14 mm<sup>2</sup> Shielded Flat Audio Cable



**CATEGORY** Shielded Flat Audio Cable (See Audio Catalogue)  
**APPLICATIONS** Sound Reproduction and Electronics.

- A:** Black Soft **PVC** Sheath.  
Outer cable Dimension 2,80x12,00 (±0,10) mm.
- B:** Each conductor have his own shielding in O.F.C. red copper spiral, covering 100%.
- C:** Core Insulation with PVC, colored Black, Red, Yellow and White.  
Diam. Ø 1,10 (±0,10) mm.
- D:** Stranded formation in O.F.C. red copper 18x0,10 mm.  
Nom. Cross section 4x0,14 mm<sup>2</sup>.

**MARKING** tasker® C 119 4x0,14 mm<sup>2</sup> O.F.C. Shielded Flat Cable  
**CUSTOM** This product may be custom produced also in **L.S.Z.H.** polymer, **PE** or **PUR**.  
**PRODUCTION**

### Cable Properties

<b>Conductor Resistance</b>	138 Ω/Km
<b>Capacity Core/Core</b>	65 pF/mt
<b>Capacity Core/Shield</b>	350 pF/mt
<b>Max Rated Voltage</b>	49V
<b>Operative Temperature</b>	-15/+70°C

<b>USE</b>	<b>X</b>	Indoor	Interno Edificio	<b>INSTALLATION</b>	<b>X</b>	Fixed	Fissa	<b>INFORMATION</b>	<b>X</b>	RoHS2 Compliant
<b>Impiego</b>		Outdoor Limited	Esterno Limitato	<b>Posa</b>	<b>X</b>	Restricted Mobile	Mobile Limitata	<b>Informazioni</b>	<b>X</b>	Ver. A / 16.05.17
		Outdoor	Esterno			Mobile	Mobile			
		Outdoor Direct Burial	Esterno Interrato			Mobile in Drag Chain	Mobile in Catena			