

MILAN S.r.l. a socio unico

Head Office – Export department:
 Viale Europa, 74
 20090 Cusago (MI) Italy
 T. +39 02 9039.4556-4158
 F. +39 02 9039.4551
 www.taskercables.com

Ufficio Commerciale e Centro Distribuzione
 Viale Europa 72 Strada F12
 20090 Cusago (MI) Italy
 T. +39 02 9039.0037-0059
 F. +39 02 9039.0049
 www.tasker.it



Technical Datasheet

tasker® C228 1x0,08 (75Ω) + 2x0,14 mm² Special Video Flat Divisible Cable

	E	F	G
Video Section			
A			
Audio Section			
	B	C	D

CATEGORY Video + Audio Cables (See Video Catalogue)
APPLICATIONS Video and Audio Stereo assembly

A: Black Soft **PVC** Sheath.
 Outer Dimension: 3,40x10,40 (±0,20) mm.

Audio Section:

- B:** Spiral shielding in of O.F.C. red copper, covering 100%.
- C:** Insulations with PVC, colored one red and one white.
 Diam. Ø 1,50 (±0,20) mm.
- D:** Stranded O.F.C. red copper formation 18x0,10 mm..
 Nom. Cross section 2x0,14 mm².

Video Section:

- E:** Spiral shielding in of O.F.C. tinned copper, covering 100%.
- F:** Insulation with yellow PEE. Diam. Ø 1,50 (±0,20) mm.
- G:** Stranded O.F.C. red copper formation 10x0,10 mm..
 Nom. Cross section 1x0,08 mm² (75Ω)

MARKING **tasker® C 228 1x0,08 (75W) + 2x0,14 mm² O.F.C. Video + Audio Cable**
 Made in Italy

MILAN S.r.l. a socio unico

Head Office – Export department:

Viale Europa, 74
20090 Cusago (MI) Italy
T. +39 02 9039.4556-4158
F. +39 02 9039.4551
www.taskercables.com

Ufficio Commerciale e Centro Distribuzione

Viale Europa 72 Strada F12
20090 Cusago (MI) Italy
T. +39 02 9039.0037-0059
F. +39 02 9039.0049
www.tasker.it

**CUSTOM
PRODUCTION**

This product may be custom produced also in **L.S.Z.H.** polymer, **PE** or **PUR**.

Audio Section Properties

Conductor Resistance	138 Ω/Km
Capacity Core/Core	50 pF/m
Capacity Core/Shield	250 pF/m

Video 75 Ω properties

Conductor Resistance	203 Ω/Km
Impedence	75 Ω
Velocity of Propagation	66 %
Capacity Core/Shield	67 pF/m

General Properties:

Max rated Voltage	49 V
Operative Temperature	-15/+70°C

Attenuation dB/100 mt.

50 MHz	19,5
100 MHz	28,5
200 MHz	41,7
400 MHz	60,2
800 MHz	87,3
1000 MHz	103,0

USE	X	Indoor	Interno Edificio	INSTALLATION	X	Fixed	Fissa	INFORMATION	X	RoHS2 Compliant
Impiego		Outdoor Limited	Esterno Limitato	Posa	X	Restricted Mobile	Mobile Limitata	Informazioni	X	Ver. A / 26.05.17
		Outdoor	Esterno			Mobile	Mobile			
		Outdoor Direct Burial	Esterno Interrato			Mobile in Drag Chain	Mobile in Catena			