

WISI DB 10 1006

TERR/BK antenna socket, 2-hole stub socket 5...1006 MHz



Description

The DB 10 1006 is a TER terminating outlet with filter. It has a small connection loss at TV as FM 0.5 / 1.5 dB. The housing has a very high stability and ensures high shielding (class A). Thanks to a flat design its space-saving architecture and IEC socket / plug, a secure connection is ensured.

At a glance:

- 1x IEC-male, 1x IEC-female

Technical data	
Inputs	
Frequency range	5...1006 MHz
Outputs	
Frequency range TV	5...68/132...1006 MHz
Frequency range FM	87,5...108 MHz
Insertion loss TV	0.5 dB
Insertion loss FM	1.5 dB
Decoupling TV-FM	≥20 dB
Return loss TV	Cat C
Return loss Input	Cat B
Return loss FM	Cat C
Connectors	
Outer conductor clamp	7.5 mm
Inner conductor clamp	0,8...1,3 mm
IEC socket	1 pcs.
IEC-plug	1 pcs.
General data	
Screening factor	>85 dB (class A)
Dimensions (width x height x depth)	70 x 70 x 22 mm
Installation depth	35 mm

Packaging data	
Sales unit	10 pcs.
Dimensions (WxHxD) sales unit	212 x 148 x 78 mm
Packaging volume sales unit	dm ³
Gross weight sales unit	0.110 kg
Shipping unit	100 pcs.
Dimensions (WxHxD) shipping unit	mm
Packaging volume shipping package	0.22 dm ³
Gross weight shipping unit	0.11 kg
EAN	4010056723262
Article number	72326
Customs tariff number	85291095