


# WISI DB 33

Antenna sockets, 2-hole stub sockets



## Description

The DB 33 is a 2-hole wall outlet for TV and SAT. In SAT connecting a DC bypass is integrated which allows the passage of the required switching voltages. The housing has a very high stability and ensures high shielding properties (Class A). Thanks to a flat and space saving construction and through the IEC socket / plug, a secure connection is ensured.

## At a glance:

- 1x IEC-male, 1x IEC-female

## Technical data

Inputs	
Frequency range	47...2150 MHz
Outputs	
Frequency range TV	47...862 MHz
Frequency range SAT	950...2150 MHz
Insertion loss TV	≤1,5/<4,0 dB
Insertion loss FM	2.5 dB
Insertion loss SAT	<2,5/≤1,5 dB
Decoupling IN-SAT 47-862 MHz	≥20 dB
Decoupling IN-TV 950-2150 MHz	≥20 dB
Decoupling TV-SAT	≥20 dB
Return loss TV	Cat C
Return loss Input	Cat B
Return loss SAT	Cat C
Power passing	24 V DC (remote power 500 mA)
Connectors	
Outer conductor clamp	7.5 mm
Inner conductor clamp	0,8...1,3 mm
IEC socket	1 pcs.
IEC-plug	1 pcs.
General data	
Screening factor	>85 dB (class A)
Dimensions (width x height x depth)	70 x 70 x 22 mm
Installation depth	35 mm

## Packaging data

Sales unit	10 pcs.
Dimensions (WxHxD) sales unit	212 x 148 x 78 mm
Packaging volume sales unit	dm <sup>3</sup>
Gross weight sales unit	0.110 kg
Shipping unit	100 pcs.
Dimensions (WxHxD) shipping unit	mm
Packaging volume shipping package	0.24 dm <sup>3</sup>
Gross weight shipping unit	0.11 kg
EAN	4010056105471
Article number	10547
Customs tariff number	85291095