

MK 8-00 DVB headend



- ✓ Eight independent multituner inputs
- ✓ Transmodulates 8 × DVB-S/S2/S2x/T/T2/C into 8 × DVB-C or DVB-T
- ✓ Output modulation configurable
- ✓ Remux | Crossmultiplex
- ✓ Class A according to EN 50083-2
- ✓ Web-based configuration, remote maintenance (SMARTPortal)
- ✓ Supports SNMPv1 and SNMPv2c
- ✓ Can be used for wall mounting or as a 19" unit

Order information

Type	MK 8-00
Order no.	MK00800
GTIN	7611682005950
PE	1
VE	1
EU customs tariff number	85256000



Technical data

Inputs

Number of tuner	8 × DVB-S/S2/S2x/T/T2/C
Connector	8 × F-female
Frequency range	900...2150 MHz @ DVB-S/S2/S2X 50...898 MHz @ DVB-C 50...898 MHz @ DVB-T/T2
Channel bandwidth	5/6/7/8 MHz @ DVB-T/T2
Input level	43...84 dBμV @ DVB-S/S2/S2X 49...84 dBμV @ DVB-C 39...84 dBμV @ DVB-T/T2
LNB voltage	13/17 V; 22 kHz on/off; DiSEqC 1.0
Max. LNB current	150 mA per input 1000 mA per device

Input modulation

Type	QPSK/8PSK/ 8APSK/16APSK/32APSK @ DVB-S/S2/S2X QAM16, QAM32, QAM64, QAM128, QAM256 @ DVB-C QPSK, QAM16, QAM66 @ DVB-T QPSK, QAM16, QAM64, QAM256 @ DVB-T2
Compliance	DVB-S = EN 300 421 DVB-S2 = EN 302 307-1V1.4.1 DVB-S2X = EN 302 307-2V1.1.1 DVB-C = EN 300 429/ITU-TJ.83 Annex A/C DVB-T = EN 300 744 DVB-T2 = ETSI EN 302 755
Supported input transport streams	MPEG-2 ISO/IEC 13818 MPEG-4 ISO/IEC 14496
Error correction	auto
Symbol rate	1,5...45 MS/s (<40MSymbol/s in 32APSK) @ DVB-S 1...7,2 Mbaud @ DVB-C

Output


Number of channels	8 × DVB-C/DVB-T
Frequency range	109...1006 MHz @ DVB-C 109...862 MHz @ DVB-T
Channels selectable	S2...K87 @ DVB-C S2...K69 @ DVB-T
Channel bandwidth	7 MHz, 8 MHz @ DVB-T
Possible frequency shift	-4...+4 MHz (0.5 MHz steps)
Connector	1 × F-female
Test port	1 × F-female (-30 dB)
Impedance	75 Ω
Output level adjustable	80...100 dBμV @ DVB-C 77...98 dBμV @ DVB-T

Output modulation

Compliance	DVB-T (EN 300 744) DVB-C (EN 300 429/ITU-TJ.83 AnnexA/C)
Type	32QAM, 64QAM, 128QAM, 256-QAM @ DVB-C 16QAM, 64QAM @ DVB-T

MER	≥ 40 dB @ DVB-C ≥ 36 dB @ DVB-T
Bit rate, max	50,87 Mbps @ DVB-C 31,668 Mbps @ DVB-T
FFT	2K, 8K mode @ DVB-T
FEC	1/2, 2/3, 3/4, 5/6, 7/8 @ DVB-T
Guard interval	1/4, 1/8, 1/16, 1/32
Symbol rate	1...7,5 MBauds/s
Interfaces	
Configuration interface	1 × RJ-45
Compliance configuration interface	IEEE 802.3, 100 Base-T
Supported configuration protocols	HTTP, SNMP v1, SNMP, v2c, AXING SMARTPortal*
General	
Operating voltage	100...240 VAC/50...60 Hz
Power consumption	50 W
Operating temperature range (acc. to EN 60065)	-10°C...+50°C
Dimensions (W × H × D) appr.	480 × 253 × 47 mm
Weight	2,55 kg
Comments	* encrypted, cloud-based application for configuration, monitoring and remote maintenance

Example of use



Suitable products

[MKS 1-00 Software extension to edit a NIT](#)

[MKS 1-01 Software extension for PID filtering](#)

[MKS 8-16 Software extension from 8 to 16 output modulators](#)