

MILAN S.r.l. a socio unico

Head Office – Export department:
 Viale Europa, 74
 20090 Cusago (MI) Italy
 T. +39 02 9039.4556-4158
 F. +39 02 9039.4551
 www.taskercables.com

Ufficio Commerciale e Centro Distribuzione
 Viale Europa 72 Strada F12
 20090 Cusago (MI) Italy
 T. +39 02 9039.0037-0059
 F. +39 02 9039.0049
 www.tasker.it

Technical Datasheet:



tasker® RG 58 CU Coaxial 50Ω Mil. C17F Standard Cable



A	B	C	D
---	---	---	---

CATEGORY Coaxial cable 50 Ω (See Video Catalogue)

- A:** Black Soft **PVC** Sheath.- Outer Diam. Ø 5,00 (±0,10) mm.
- B:** Shielding O.F.C. tinned copper braid covering 88%.
- C:** Core Insulation with transparent compact PE.
Diam. Ø 3,00 (±0,10) mm
- D:** O.F.C. tinned copper stranded formation, 19x0,18 mm.
Nom. Cross section 1x0,48 mm².

MARKING **tasker®** RG 58 CU Mil. C/17 F 50 Ω

CUSTOM This product is also available in **L.S.Z.H., PE, PUR**, with or without **Steel Armor**.

Cable Properties

Conductor Resistance	40 Ω/Km ± 5%
Capacity Core/Shield	100 pF/mt
Velocity of Propagation	66%
Impedance	50 Ω ± 3%
Max Rated Voltage	2.000 V
Operative Temperature	-15/+70 C°

Attenuation dB/100 mt.

50 MHz	9,70
100 MHz	13,90
200 MHz	20,40
400 MHz	30,00
800 MHz	45,10
1000 MHz	51,80

USE	X	Indoor	Interno Edificio	INSTALLATION	X	Fixed	Fissa	INFORMATION	X	RoHS2 Compliant
Impiego	X	Outdoor Limited	Esterno Limitato	Posa	X	Flexible Limited	Flessibilità limitata	Informazioni	X	Ver. C / 27.06.16
		Outdoor Direct Burial	Esterno Interrato		X	Dynamic (Drag Chain)	Mobile in Catena			
				Dynamic (Torsion)	Mobile in Torsione		