

MILAN S.r.l. a socio unico

Head Office – Export department:
 Viale Europa, 74
 20090 Cusago (MI) Italy
 T. +39 02 9039.4556-4158
 F. +39 02 9039.4551
 www.taskercables.com

Ufficio Commerciale e Centro Distribuzione
 Viale Europa 72 Strada F12
 200 Cusago (MI) Italy
 T. +39 02 9039.0037-0059
 F. +39 02 9039.0049
 www.tasker.it

Technical Datasheet

tasker® RG 59 Flex -Coaxial Cable 75 Ω



A	B	C	D
---	---	---	---

CATEGORY
APPLICATIONS

Coaxial cable 75 Ω (See Video Catalogue)
 Premade video Cables and Broadcast.

- A:** PVC Sheath available in different color.
Outer cable Diam. Ø 6,10 (±0,10) mm.
- B:** Shielding in O.F.C. red copper braid covering 90%.
- C:** Core Insulation with transparent PE. Diam. Ø 3,70 (±0,10) mm.
- D:** Stranded O.F.C. red copper formation 7x0,20 mm.
Nom. Cross section 1x0,22 mm².

MARKING

tasker® RG 59 FLEX 1x0,22 mm² (75Ω) Broadcast Video Cable
 - Made in Italy

CUSTOM
PRODUCTION

This product may be custom produced also in **PE**, with or without
 Metallic Armor.

Cable Properties

Conductor Resistance	75 Ω/Km
Capacity Core/Shield	67 pF/mt
Velocity of Propagation	66%
Impedance	75 Ω
Max Rated Voltage	2.000 V
Operative Temperature	-15/+70°C

Attenuation dB/100 m.

50 MHz	7,4
100 MHz	10,7
200 MHz	15,7
400 MHz	22,7
800 MHz	33,6
1000 MHz	38,0

USE	X	Indoor	Interno Edificio	INSTALLATION	X	Fixed	Fissa	INFORMATION	X	RoHS3 Compliant
Impiego		Outdoor Limited	Esterno Limitato	Posa	X	Restricted Mobile	Mobile Limitata	Informazioni	X	Ver. B / 16.04.19
		Outdoor	Esterno			Mobile	Mobile			
		Outdoor Direct Burial	Esterno Interrato			Mobile in Drag Chain	Mobile in Catena			