

<sup>7</sup> 8 G. SC1-N-PC10	
DIMENSIONS OF STRIPPED RG58 COAX CABLE PREPARED FOR ASSEMBLY.	A
	В
.3 GHz. MUST CONFORM TO THESE STANDARD INTERFACE IN CAPTIVE AFTER ASSEMBLY OF CONNECTOR. 5 TO BE SUPPLIED ASSEMBLED TO CONNECTOR. PLING NUT: BRASS CW603N (CuZn36Pb3), BRASS	С
PPROVED EQUIVALENT. SS CW614N (CuZn39Pb3) OR APPROVED EQUIVALENT. ASS CW603N (CuZn36Pb3), BRASS CW614N (CuZn39Pb3), NT. PLING NUT: 2.54μm MIN.) OVER COPPER (1.27μm MIN.) um MIN.) OVER NICKEL PHOSPHOROUS ALLOY (2.03μm	D
PPER ALLOY (2.54µm MIN.) OVER COPPER (1.27µm MIN.) SODY. FTER PLATING. OVED BY PANORAMA ANTENNAS Q.C. BEFORE DN. MUST BE RoHS2 (DIRECTIVE 2011/65/EU) COMPLIANT ANY SUBSTANCES OF VERY HIGH CONCERN (SVHCs) POLY-AROMATIC HYDROCARBONS (PAHs), OR LLUTANTS (POPs) CONTROLLED BY THE STOCKHOLM	E
MPLIANCE WITH THE USA DODD-FRANK ACT (SECTION M AND TUNGSTEN CONTAINED IN PANORAMA Y TRACEABLE TO A SMELTER APPROVED BY THE G INITIATIVE (www.comflictfreesmelter.org).	
VED D.O. CHECK IC SCALE DIMENSIONS	
$A N O R A M A \qquad \bigcirc \qquad A N T E N N A$	S