

MILAN S.r.l. a socio unico

**Head Office – Export department:**  
 Viale Europa, 74  
 20090 Cusago (MI) Italy  
 T. +39 02 9039.4556-4158  
 F. +39 02 9039.4551  
 www.taskercables.com


**Ufficio Commerciale e Centro Distribuzione**  
 Viale Europa 72 Strada F12  
 20090 Cusago (MI) Italy  
 T. +39 02 9039.0037-0059  
 F. +39 02 9039.0049  
 www.tasker.it



## Technical Datasheet

# tasker® TSK816 – 16x2x0,14 mm<sup>2</sup>

### Digital Audio Multipair Cable 110 Ohm AES/EBU



**NOTE**  
**CATEGORY**  
**APPLICATIONS**

The picture don't represent the real number of conductors  
 Digital Multipair Audio Cable (See Audio Catalogue)  
 Audio Mixers, Benches and Audio Balanced multi sockets.

- A:** Soft Black **PVC** Sheath.  
Outer cable Ø: 17,90 (±0,10) mm.
- B:** The single pairs are isolated with black **PVC**, numbered from one to the number of elements and wrapped together with polyester base tape.  
Diam. Ø 3,20 (±0,10) mm.
- C:** The single pair are shielded with aluminum tape covering 100% + tinned copper Drain Wire.
- D:** The single cores are insulated with **foam PE**, colored one white and one red, and wrapped with not weaved polyester base tape.  
Diam. Ø 1,20 (±0,10) mm.



MILAN S.r.l. a socio unico

**Head Office – Export department:**

Viale Europa, 74  
20090 Cusago (MI) Italy  
T. +39 02 9039.4556-4158  
F. +39 02 9039.4551  
www.taskercables.com

**Ufficio Commerciale e Centro Distribuzione**

Viale Europa 72 Strada F12  
20090 Cusago (MI) Italy  
T. +39 02 9039.0037-0059  
F. +39 02 9039.0049  
www.tasker.it

**E:** O.F.C. tinned copper formation 18x0,10 mm.  
Nom. Cross section 16x2x0,14 mm<sup>2</sup>.

**MARKING**

**tasker®** TSK 816 16x2x0,14 mm<sup>2</sup> - EXTRA FLEX DIGITAL AUDIO MULTIPAIR CABLE - MADE IN ITALY

**CUSTOM PRODUCTION**

This product may be custom produced also in **L.S.Z.H.** polymer, **PE, PUR**, with or without Metallic Armor.

**Cable Properties**

<b>Conductor Resistance</b>	138,00 Ω/Km
<b>Capacity Core/Core</b>	50 pF/mt
<b>Capacity Core/Shield</b>	100 pF/mt
<b>Impedance</b>	110 Ω
<b>Max Rated Voltage</b>	49 V
<b>Operative Temperature</b>	-15/+70°C

<b>USE</b>	<b>X</b>	Indoor	Interno Edificio
<b>Impiego</b>		Outdoor Limited	Esterno Limitato
		Outdoor	Esterno
		Outdoor Direct Burial	Esterno Interrato

<b>INSTALLATION</b>	<b>X</b>	Fixed	Fissa
<b>Posa</b>	<b>X</b>	Restricted Mobile	Mobile Limitata
		Mobile	Mobile
		Mobile in Drag Chain	Mobile in Catena

<b>INFORMATION</b>	<b>X</b>	RoHS2 Compliant
<b>Informazioni</b>	<b>X</b>	Ver. A / 16.05.16

