

MILAN S.r.l. a socio unico

Head Office – Export department:
 Viale Europa, 74
 20090 Cusago (MI) Italy
 T. +39 02 9039.4556-4158
 F. +39 02 9039.4551
 www.taskercables.com

Ufficio Commerciale e Centro Distribuzione
 Viale Europa 72 Strada F12
 20090 Cusago (MI) Italy
 T. +39 02 9039.0037-0059
 F. +39 02 9039.0049
 www.tasker.it



Technical Datasheet

tasker® C120 - 6x0,14 mm²

Spiral Shielded Multi-Conductor Cable



A	B	C	D	E
---	---	---	---	---

CATEGORY Spiral Shielded Cables (See Audio Catalogue)
APPLICATIONS Sound Reproduction and Electronics.

- A:** Black Soft **PVC** Sheath.
Outer Diam. Ø 9,30 (±0,20) mm.
- B:** Inner sheaths on each conductor with red **PVC**.
Diam. Ø 2,20 (±0,10) mm.
- C:** O.F.C. red copper spiral Shielding, covering 100%.
- D:** **PVC** Core Insulation. Diam. Ø 1,10 (±0,10) mm.
Color Code: Black, White, Red, Yellow, Green, Blue.
- E:** O.F.C. Red Copper stranded formation 18x0,10 mm.
Nom. Cross section 6x0,14 mm².

MARKING **tasker®** C120 6x0,14 mm² O.F.C. Individually Shielded Cable
CUSTOM This product may be custom produced also in **L.S.Z.H.** polymer, **PE, PUR,**
PRODUCTION with or without Metallic Armor.

Cable Properties

Conductor Resistance	138 Ω/Km
Capacity Core/Core	80 pF/m
Capacity Core/Shield	340 pF/m
Max Rated Voltage	49 V
Operative Temperature	-15/+70° C

USE	X	Indoor	Interno Edificio	INSTALLATION	X	Fixed	Fissa	INFORMATION	X	RoHS3 Compliant
Impiego		Outdoor Limited	Esterno Limitato	Posa	X	Flexible Limited	Flessibilità limitata	Informazioni	X	Ver. B / 12.06.19
		Outdoor	Esterno			Dynamic (Drag Chain)	Mobile in Catena			
		Outdoor Direct Burial	Esterno Interrato			Dynamic (Torsion)	Mobile in Torsione			