

MILAN S.r.l. a socio unico

Head Office – Export department:
 Viale Europa, 74
 20090 Cusago (MI) Italy
 T. +39 02 9039.4556-4158
 F. +39 02 9039.4551
 www.taskercables.com

Ufficio Commerciale e Centro Distribuzione
 Viale Europa 72 Strada F12
 20090 Cusago (MI) Italy
 T. +39 02 9039.0037-0059
 F. +39 02 9039.0049
 www.tasker.it



Technical Datasheet

tasker® C145 – 5x0,08 mm² (75 Ω)

Special Multi Mini Coax Video cable



A	B	C	D	E	F
---	---	---	---	---	---

CATEGORY Coaxial cable 75 Ω (See Video Catalogue)
APPLICATIONS Professional video transmission systems and monitors.

- A:** Black **Flame Retardant PVC** Sheath. Outer Diam. Ø 9,20 (±0,20) mm.
- B:** Grouping with un-weaved polyester tape.
- C:** Soft **PVC** Sheath on single conductors. Diam. Ø 2,40 (±0,20) mm.
Colored: Red, Green, Blue, Black and White.
- D:** Shielding in O.F.C. tinned copper braid covering 90%.
- E:** Core Insulation with PPE – Diam. Ø 1,40 (±0,20) mm.
- F:** Stranded formation in O.F.C. tinned copper, 7x0,12 mm.
Nom. Cross section 5x0,08 mm² (75Ω).

MARKING **tasker®** C 145 5x0,75 Ω PROFESSIONAL HIGH DEFINITION MULTIVIDEO CABLE
 FirestoP® CEI 20-22/II° MADE IN ITALY

CUSTOM PRODUCTION This product may be custom produced also in **L.S.Z.H.** polymer, **PE, PUR**, with or without Metallic Armor.

Cable Properties

Conductor Resistance	203 Ω/Km
Capacity Core/Shield	67 pF/mt
Velocity of Propagation	66%
Impedance	75 Ω
Max Rated Voltage	49 V
Operative Temperature	-20/+70°C

Attenuation dB/100 mt.

50 MHz	19,70
100 MHz	28,70
200 MHz	42,00
400 MHz	61,20
800 MHz	88,50
1000 MHz	105,00

USE	X	Indoor	Interno Edificio	INSTALLATION	X	Fixed	Fissa	INFORMATION	X	RoHS2 Compliant
Impiego	X	Outdoor Limited	Esterno Limitato	Posa	X	Flexible Limited	Flessibilità limitata	Informazioni	X	Ver. A / 07.12.2015
		Outdoor	Esterno			Dynamic (Drag Chain)	Mobile in Catena			
		Outdoor Direct Burial	Esterno Interrato			Dynamic (Torsion)	Mobile in Torsione			