

MILAN S.r.l. a socio unico

Head Office – Export department:
 Viale Europa, 74
 20090 Cusago (MI) Italy
 T. +39 02 9039.4556-4158
 F. +39 02 9039.4551
 www.taskercables.com

Ufficio Commerciale e Centro Distribuzione
 Viale Europa 72 Strada F12
 20090 Cusago (MI) Italy
 T. +39 02 9039.0037-0059
 F. +39 02 9039.0049
 www.tasker.it

Technical Datasheet

tasker® C300 – 1x0,22 mm²

Guitar Cable with Carbon Screen



A	B	C	D	E
---	---	---	---	---

CATEGORY Instrumental Cable (See Audio Catalogue)
APPLICATIONS Premade cables for instrumental cable like Guitar, Bass and Keyboards

- A:** Black Soft PVC Sheath. Outer Diam. Ø 6,00 (±0,10) mm.
- B:** First shielding with O.F.C. red copper Spiral covering 100%.
- C:** Conductive carbon screen covering.
- D:** Transparent PPE insulation. Diam. Ø 1,50 (±0,10) mm.
- E:** O.F.C. stranded tinned copper formation 7x0,20 mm.
Nom. Cross section 1x0,22 mm².

MARKING tasker® C300 1X0.22 - 24 AWG O.F.C. Professional Noiseless Guitar Cable
 Low Capacity Made in Italy

CUSTOM PRODUCTION This product may be custom produced also in **L.S.Z.H.** polymer, **PE, PUR,** with or without Metallic Armor.

Cable Properties

Conductor Resistance	79,15 Ω/km
Capacity Core/Shield	88 pF/m
Max Rated Voltage	49 V
Operative Temperature	-15/+70°C

USE	X	Indoor	Interno Edificio	INSTALLATION	X	Fixed	Fissa	INFORMATION	X	RoHS2 Compliant
Impiego		Outdoor Limited	Esterno Limitato	Posa	X	Restricted Mobile	Mobile Limitata	Informazioni	X	Ver. A / 16.05.16
		Outdoor	Esterno			Mobile	Mobile			
		Outdoor Direct Burial	Esterno Interrato			Mobile in Drag Chain	Mobile in Catena			