

TAPS



DQC 616 · DQC 620 · DQC 624

- ✓ QuiCoax connection system
- ✓ 6 Outputs
- ✓ Low insertion loss
- ✓ DC pass in trunk line



EKSELANS BY ITS



DQC 616

01



Reduce to minimum installation time

02



No need of tools

03



Guarantees an excellent connected and minimizes the space

04



Very high shielding factor CLASS A +10dB throughout the band

05



Eliminate the use of connectors and associated costs

06



QuiCoax, the new Standard of Connection



TECHNICAL TABLE

Reference	DQC616	DQC620	DQC624
CODE	142020	142021	142022
LOSS			
Insertion loss (in-out) 5-47 MHz	<4.1 dB	<1.8 dB	<1.1 dB
Insertion loss (in-out) 47-950 Mhz	<4.1 dB	<2.7 dB	<1.8 dB
Insertion loss (in-out) 950-2150 MHz	<4.2 dB	<3.6 dB	<2.5 dB
Insertion loss (in-out) 2150-2400 Mhz	<4.4 dB	<3.9dB	<2.8 dB
Tap loss (in-tap) 5-47 MHz	16 dB ±1.5 dB	20 dB ±1.5 dB	24 dB ±1.5 dB
Tap loss (in-tap) 47-950 Mhz	16 dB ±1.5 dB	20 dB ±1.5 dB	24 dB ±1.5 dB
Tap loss (in-tap) 950-2150 MHz	16 dB ±1.5 dB	20 dB ±1.5 dB	24 dB ±1.5 dB
Tap loss (in-tap) 2150-2400 Mhz	16 dB ±1.5 dB	20 dB ±1.5 dB	24 dB ±1.5 dB
ISOLATION			
Isolation (tap-tap) 5-47 MHz	>25 dB	>25 dB	>25 dB
Isolation (tap-tap) 47-950 MHz	>22 dB	>23 dB	>25 dB
Isolation (tap-tap) 950-2150 MHz	>20 dB	>23 dB	>25 dB
Isolation (tap-tap) 2150-2400 MHz	>20 dB	>25 dB	>28 dB
Isolation (tap-out) 5-47 MHz	>23 dB	>35 dB	>35 dB
Isolation (tap-out) 47-950 MHz	>23 dB	>30 dB	>30 dB
Isolation (tap-out) 950-2150 MHz	>24 dB	>24 dB	>30 dB
Isolation (tap-out) 2150-2400 MHz	>25 dB	>24 dB	>28 dB
RETURN LOSS			
Return loss 5-47 MHz	>15 dB	>15 dB	>15 dB
Return loss 47-950 MHz	>15 dB	>15 dB	>15 dB
Return loss 950-2150 MHz	>15 dB	>15 dB	>15 dB
Return loss 2150-2400 MHz	>12 dB	>12 dB	>12 dB
OPERATIONAL			
Impedance	75 Ω	75 Ω	75 Ω
Application	SAT, MATV 2.4Ghz +DC	SAT, MATV 2.4Ghz +DC	SAT, MATV 2.4Ghz +DC
Screening Efficiency	EN50083-2 Class A +10dB	EN50083-2 Class A +10dB	EN50083-2 Class A +10dB
DC Passthrough	Yes (max. 500mA)	Yes (max. 500mA)	Yes (max. 500mA)
Environment	Indoor	Indoor	Indoor
CABLE CONNECTION			
Number of inputs	1	1	1
Number of outputs	1	1	1
Number of taps	6	6	6
Connection Type	QuiCoax	QuiCoax	QuiCoax
MECHANICAL			
Product Depth	16 mm	16 mm	16 mm
Product Height	38 mm	38 mm	38 mm
Product Width	103 mm	103 mm	103 mm
Packing QTY	1	1	1
Net Weight	0.114kg	0.114kg	0.114kg

Ekselans by ITS

Test of: Coupling transfer function (Ed.2)

Information for test

Test Job: 3000 Operator: J.M. Measurement: 05.02.2020 11:47:46
 Test set-up: triaxial cell 1000/150+TEPASS 3000 A++
 Remark: triaxial cell 1000/150

Device under test

Item Number: 0000 Cable type: EK RQC 2-1 cell 1000/15
 Type: coaxial Zw: 75.0 Ohm
 Test length: 1.00 m Eps r: 1.5



Test parameter

Start frequency: 10.0 kHz	Gen. Power: 0.0 dBm	Add. parameter of transfer impedance:
Stop frequency: 3.0 GHz	Atten.(P1/P2): 0.0 dB	Test-setup: Short-Matched
Number of points: 801		R1(Z1): 75.0 Ohm
Distance of points: log		R2: 0.0 Ohm Eps r2: 0.0
IF-BW: 10 Hz		Rp: - - - Z2: 0.0 Ohm
Z(NWA): 50.0 Ohm		Rs: - - - lex: 0.0 m

Test diagram

Coupling transfer function (Ed.2) EK RQC 2-1 cell 1000/15

