

WISI MK 96 L 0500

Coaxial cable halogen-free



Description

VDE-inspection IEC 60332

At a glance:

- Triple shield

Technical data

Installation	Indoor installation
Screening construction	3-way
Inner conductor material	Cu-core
Dielectric	Cell PE/copper braiding MK 15 + Al-foil
Outer conductor diameter	mm Bonded aluminium foil / copper braid
Outer jacket material	LSZH-Compound
Inner conductor diameter	1.02 mm
Dielectricum diameter	4.75 mm
Outer jacket diameter	6.5 mm
Loop resistance	34.5 Ω /km
Loss 5 MHz	1.6 dB (100m)
Attenuation 50 MHz	4.1 dB (100m)
Attenuation 600 MHz	14.8 dB (100m)
Attenuation 1000 MHz	19.4 dB (100m)
Loss 2200 MHz	29.7 dB (100m)
Return loss 5...862 MHz	>30 dB
Return loss 862...2500 MHz	>20 dB
Screening factor (EMC)	\geq 115 dB
Coupling resistance 5...30 MHz	\leq 5 m Ω /m

General data

Color	White
Cable weight	43 kg/km
Bending radius single / multiple classification	35/75 mm Class A

Packaging data

Sales unit	500 m (plastic drum)
Dimensions (WxHxD) sales unit	340 x 400 x 400 mm
Packaging volume sales unit	dm ³
Gross weight sales unit	0.043 kg
Shipping unit	500 m (1 x 500 m)
Dimensions (WxHxD) shipping unit	mm
Packaging volume shipping package	dm ³
Gross weight shipping unit	0.043 kg
EAN	4010056184599
Article number	18459
Customs tariff number	85442000