

DIN RAIL POWER SUPPLY, 15W



GENERAL

| | |
|--|----------------|
| Input voltage | 90 - 264 VAC |
| Input frequency | 50/60 Hz |
| Input current | 0.5 A |
| Output voltage | 24 VDC |
| Output current | 0.63 A |
| Input voltage absolute maximum | 85 - 264 VAC |
| Input frequency absolute maximum | 47 - 63 Hz |
| Inrush current | 45 A |
| Output voltage absolute maximum | 21.6 - 29 VDC |
| Short circuit protection | ✓ |
| HIPOT (dielectric withstand test) – Primary to Secondary | 3 kVAC |
| Input connector | Screw terminal |
| Output connector | Screw terminal |
| Weight | 78 g |

Certification

Safety: EN 62368-1:2014+A11:2017
 BS EN 62368-1:2014+A11:2017
EMC: EN 55032:2015+A11:2020+A1:2020
 EN 55035:2017+A11:2020
 EN IEC 61000-3-2:2019+A1:2021
 EN 61000-3-3:2013+A1:2019+A2:2021
 BS EN 55032:2015+A11:2020
 BS EN 55035:2017+A11:2020
 BS EN IEC 61000-3-2:2019+A1:2021
 BS EN 61000-3-3:2013+A1:2019

