

MILAN S.r.l. a socio unico

Head Office – Export department:
 Viale Europa, 74
 20090 Cusago (MI) Italy
 T. +39 02 9039.4556-4158
 F. +39 02 9039.4551
 www.taskercables.com

Ufficio Commerciale e Centro Distribuzione
 Viale Europa 72 Strada F12
 20090 Cusago (MI) Italy
 T. +39 02 9039.0037-0059
 F. +39 02 9039.0049
 www.tasker.it



Technical Datasheet

tasker® RG 59 Special 75 Ω Coaxial Cable



A	B	C	D
---	---	---	---

CATEGORY
APPLICATIONS

Coaxial cable 75 Ω (See Video Catalogue)
 Standard definition video applications and cable assembly

- A:** Grey Soft **PVC** Sheath - Outer Diam. Ø 6,30 (±0,20) mm.
- B:** Double Braid Shielding, one in O.F.C. tinned copper and one on red copper, both with 100% covering.
- C:** Core Insulation with transparent PE. Diam. Ø 3,70 (±0,20) mm
- D:** Stiff Wire in CW formation 1x0,58 mm.
Nom. Cross section 1x0,26 mm².

MARKING

tasker® RG59 Special 75 Ohm 100% Double Shield Coaxial Video Cable Made in Italy

CUSTOM
PRODUCTION

This product may be custom produced also in **PE**, with or without Metallic Armor.

Cable Properties

Conductor Resistance	158 Ω/Km
Capacity Core/Shield	67 pF/m
Velocity of Propagation	66%
Impedance	75 Ω
Max Rated Voltage	2.000 V
Cable signal delay	5 ns/m
Operative Temperature	-15/+70°C

Attenuation dB/100 m.

50 MHz	7,2
100 MHz	10,5
200 MHz	15,5
400 MHz	22,3
800 MHz	32,8
1000 MHz	37,0

USE	X	Indoor	Interno Edificio	INSTALLATION	X	Fixed	Fissa	INFORMATION	X	RoHS2 Compliant
Impiego	X	Outdoor Limited	Esterno Limitato	Posa	X	Restricted Mobile	Mobile Limitata	Informazioni	X	Ver. A / 16.05.16
		Outdoor	Esterno			Mobile	Mobile			
		Outdoor Direct Burial	Esterno Interrato			Mobile in Drag Chain	Mobile in Catena			